

Network Camera Sensitivity Matrix Chart

Note:
Sensitivity Specification @ 50IRE without slow shutter is strongly recommended.
On the brochure issued by sales companies can contain sensitivity specification @ other conditions
provided measuring conditions are indicated like shown below.

1.7 lx @ F1.0, Slow Shutter Off, AGC on, 50IRE
0.5 lx @ F1.0, 1/15sec, AGC on, 30IRE

The bold-faced type is a nominal value.
The following is the value which was estimated based on the typical value. (Not Assured value)

Product No. SNC-CX600		As of September 26, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	1.0	0.50	0.27	0.14	0.067	0.034	-
	30 IRE	0.5	0.3	0.2	0.07	0.04	0.02	-
Night mode (B/W)	50 IRE	1.0	0.50	0.27	0.14	0.067	0.034	-
	30 IRE	0.5	0.3	0.2	0.07	0.04	0.02	-
Common Condition: F2.0/Visibility Enhancer Off/Auto gain Max. value MAX/30 fps/White LED OFF								

Product No. SNC-EB600		As of June 28, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Common Condition: F1.0, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-EB602R		As of July 25, 2014						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0	0	0	0	0	0	-
	30 IRE	0	0	0	0	0	0	-
Common Condition: F1.2, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-EB630B		As of June 28, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.1	0.05	0.03	0.02	0.007	0.004	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0.07	0.04	0.02	0.01	0.005	0.003	-
	30 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
Common Condition: F1.2, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-EB640		As of January 19, 2017						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.01	0.005	0.003	0.002	0.0007	0.0004	-
	30 IRE	0.006	0.003	0.002	0.0008	0.0004	0.0002	-
Night mode (B/W)	50 IRE	0.007	0.004	0.002	0.001	0.0005	0.0003	-
	30 IRE	0.005	0.003	0.002	0.0007	0.0004	0.0002	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-EM600		As of June 28, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Common Condition: F1.2, View-DR OFF, VE OFF, AGC ON, 1/30s, 30 fps								

Product No. SNC-EM602R		As of September 25, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0	0	0	0	0	0	-
	30 IRE	0	0	0	0	0	0	-
Common Condition: F1.2, View-DR OFF, VE OFF, AGC ON, 1/30s, 30 fps								

Product No. SNC-EM630		As of June 28, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.1	0.05	0.03	0.02	0.007	0.004	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0.07	0.04	0.02	0.01	0.005	0.003	-
	30 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
Common Condition: F1.2, View-DR OFF, VE OFF, AGC ON, 1/30s, 30 fps								

Product No. SNC-EM632R		As of September 25, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.1	0.05	0.03	0.02	0.007	0.004	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0	0	0	0	0	0	-
	30 IRE	0	0	0	0	0	0	-
Common Condition: F1.2, View-DR OFF, VE OFF, AGC ON, 1/30s, 30 fps								

Product No. SNC-EM641		As of January 19, 2017						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.01	0.005	0.003	0.002	0.0007	0.0004	-
	30 IRE	0.006	0.003	0.002	0.0008	0.0004	0.0002	-
Night mode (B/W)	50 IRE	0.007	0.004	0.002	0.001	0.0005	0.0003	-
	30 IRE	0.005	0.003	0.002	0.0007	0.0004	0.0002	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-CX600W		As of September 26, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	1.0	0.50	0.27	0.14	0.067	0.034	-
	30 IRE	0.5	0.3	0.2	0.07	0.04	0.02	-
Night mode (B/W)	50 IRE	1.0	0.50	0.27	0.14	0.067	0.034	-
	30 IRE	0.5	0.3	0.2	0.07	0.04	0.02	-
Common Condition: F2.0/Visibility Enhancer Off/Auto gain Max. value MAX/30 fps/White LED OFF								

Product No. SNC-EB600B		As of June 28, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Common Condition: F1.0, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-EB630		As of June 28, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.1	0.05	0.03	0.02	0.007	0.004	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0.07	0.04	0.02	0.01	0.005	0.003	-
	30 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
Common Condition: F1.2, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-EB632R					As of July 25, 2014				
					Unit: lux				
Condition		Shutter Speed							
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec		
Day mode (Color)	50 IRE	0.10	0.050	0.027	0.014	0.0067	0.0034	-	
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-	
Night mode (B/W)	50 IRE	0	0	0	0	0	0	-	
	30 IRE	0	0	0	0	0	0	-	
Common Condition:		F1.2, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps							

Network Camera Sensitivity Matrix Chart

Note:
Sensitivity Specification @ 50IRE without slow shutter is strongly recommended.
On the brochure issued by sales companies can contain sensitivity specification @ other conditions provided measuring conditions are indicated like shown below.

1.7 lx @ F1.0, Slow Shutter Off, AGC on, 50IRE
0.5 lx @ F1.0, 1/15sec, AGC on, 30IRE

The bold-faced type is a nominal value.
The following is the value which was estimated based on the typical value. (Not Assured value)

Product No. SNC-HM662		As of September 26, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/5 sec				
Day mode (Color)	50 IRE	0.7	0.4	0.2	-	-	-	-
	30 IRE	0.4	0.2	0.07	-	-	-	-
Night mode (B/W)	50 IRE	0.3	0.2	0.05	-	-	-	-
	30 IRE	0.1	0.05	0.02	-	-	-	-
Common Condition: F2.0, Wide-D OFF, AGC ON, 1/30s, 10fps								

Product No. SNC-VB600B		As of October 31, 2012						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Common Condition: F1.2/View-DR Off/Visibility Enhancer Off/Auto gain control maximum rate MAX/30 fps								

Product No. SNC-VB632D		As of January 20, 2014						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.10	0.050	0.027	0.014	0.0067	0.0034	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0	0	0	0	0	0	-
	30 IRE	0	0	0	0	0	0	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-VB640		As of January 19, 2017						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.01	0.005	0.003	0.002	0.0007	0.0004	-
	30 IRE	0.006	0.003	0.002	0.0008	0.0004	0.0002	-
Night mode (B/W)	50 IRE	0.007	0.004	0.002	0.001	0.0005	0.0003	-
	30 IRE	0.005	0.003	0.002	0.0007	0.0004	0.0002	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-VB770		As of August 10, 2016						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/24 sec	1/15 sec	1/12 sec	1/1 sec		
Day mode (Color)	50 IRE	0.007	0.006	0.004	0.003	0.0003	-	-
	30 IRE	0.004	0.004	0.002	0.002	0.0002	-	-
Night mode (B/W)	50 IRE	0	0	0	0	0	-	-
	30 IRE	0	0	0	0	0	-	-
Common Condition: ISO409600, 1/30s, F1.4								

Product No. SNC-VM600B		As of October 31, 2012						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Common Condition: F1.2/View-DR Off/Visibility Enhancer Off/Auto gain control maximum rate MAX/30 fps								

Product No. SNC-VM601B		As of October 31, 2012						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Common Condition: F1.2/View-DR Off/Visibility Enhancer Off/Auto gain control maximum rate MAX/30 fps								

Product No. SNC-VM630		As of October 31, 2012						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.10	0.050	0.027	0.014	0.0067	0.0034	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0.07	0.04	0.02	0.01	0.005	0.003	-
	30 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
Common Condition: F1.2/View-DR Off/Visibility Enhancer Off/Auto gain control maximum rate MAX/30 fps								

Product No. SNC-VM632R		As of September 25, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.10	0.050	0.027	0.014	0.0067	0.0034	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0	0	0	0	0	0	-
	30 IRE	0	0	0	0	0	0	-
Common Condition: F1.2/View-DR Off/Visibility Enhancer Off/Auto gain control maximum rate MAX/30 fps								

Product No. SNC-VM642R		As of January 19, 2017						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.01	0.005	0.003	0.002	0.0007	0.0004	-
	30 IRE	0.006	0.003	0.002	0.0008	0.0004	0.0002	-
Night mode (B/W)	50 IRE	0.007	0.004	0.002	0.001	0.0005	0.0003	-
	30 IRE	0.005	0.003	0.002	0.0007	0.0004	0.0002	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-VB600		As of October 31, 2012						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
	30 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
Night mode (B/W)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Common Condition: F1.2/View-DR Off/Visibility Enhancer Off/Auto gain control maximum rate MAX/30 fps								

Product No. SNC-VB630		As of October 31, 2012						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.10	0.050	0.027	0.014	0.0067	0.0034	-
	30 IRE	0.06	0.03	0.02	0.008	0.004	0.002	-
Night mode (B/W)	50 IRE	0.07	0.04	0.02	0.01	0.005	0.003	-
	30 IRE	0.05	0.03	0.02	0.007	0.004	0.002	-
Common Condition: F1.2/View-DR Off/Visibility Enhancer Off/Auto gain control maximum rate MAX/30 fps								

Product No. SNC-VB635		As of January 27, 2014						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.04	0.02	0.02	0.006	0.003	0.002	-
	30 IRE	0.02	0.01	0.006	0.003	0.002	0.0007	-
Night mode (B/W)	50 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
	30 IRE	0.01	0.005	0.003	0.002	0.0007	0.0004	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-VB642D				As of January 19, 2017				
				Unit: lux				
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.01	0.005	0.003	0.002	0.0007	0.0004	-
	30 IRE	0.006	0.003	0.002	0.0008	0.0004	0.0002	-
Night mode (B/W)	50 IRE	0.007	0.004	0.002	0.001	0.0005	0.0003	-
	30 IRE	0.005	0.003	0.002	0.0007	0.0004	0.0002	-
Common Condition:		VE OFF, AGC ON, 1/30 s, 30 fps						

Network Camera Sensitivity Matrix Chart

Note:
Sensitivity Specification @ 50IRE without slow shutter is strongly recommended.
On the brochure issued by sales companies can contain sensitivity specification @ other conditions provided measuring conditions are indicated like shown below.

1.7 lx @ F1.0, Slow Shutter Off, AGC on, 50IRE
0.5 lx @ F1.0, 1/15sec, AGC on, 30IRE

The bold-faced type is a nominal value.
The following is the value which was estimated based on the typical value. (Not Assured value)

Product No. SNC-WR600		As of January 20, 2015						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.2	0.1	0.06	0.03	0.02	0.007	-
	30 IRE	0.12	0.060	0.032	0.016	0.0080	0.0040	-
Night mode (B/W)	50 IRE	0.015	0.0075	0.0040	0.0020	0.0010	0.00050	-
	30 IRE	0.009	0.005	0.003	0.002	0.0006	0.0003	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-WR602C		As of January 20, 2015						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.2	0.1	0.06	0.03	0.02	0.007	-
	30 IRE	0.12	0.060	0.032	0.016	0.0080	0.0040	-
Night mode (B/W)	50 IRE	0.015	0.0075	0.0040	0.0020	0.0010	0.00050	-
	30 IRE	0.009	0.005	0.003	0.002	0.0006	0.0003	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-WR632		As of September 26, 2013						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	1.4	0.70	0.38	0.19	0.094	0.047	-
	30 IRE	1.0	0.50	0.27	0.14	0.067	0.034	-
Night mode (B/W)	50 IRE	0.15	0.075	0.040	0.020	0.010	0.0050	-
	30 IRE	0.1	0.05	0.03	0.02	0.007	0.004	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-XM631		As of January 20, 2014						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Night mode (B/W)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Common Condition: F2.0, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-XM636		As of July 25, 2014						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Night mode (B/W)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Common Condition: F2.2, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. UMC-S3C		As of October 21, 2016						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/20 sec	1/15 sec	1/10 sec	1/6 sec	1/4 sec	
Day mode (Color)	50 IRE	0.007	0.005	0.004	0.003	0.002	0.001	-
	30 IRE	0.004	0.003	0.002	0.002	0.0008	0.0006	-
Night mode (B/W)	50 IRE	0	0	0	0	0	0	-
	30 IRE	0	0	0	0	0	0	-
Common Condition: ISO409600, 1/30s, F1.4								

		Unit: lux						
Condition		Shutter Speed						
		-	-	-	-	-	-	-
Day mode (Color)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Night mode (B/W)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Common Condition:								

		Unit: lux						
Condition		Shutter Speed						
		-	-	-	-	-	-	-
Day mode (Color)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Night mode (B/W)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Common Condition:								

		Unit: lux						
Condition		Shutter Speed						
		-	-	-	-	-	-	-
Day mode (Color)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Night mode (B/W)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Common Condition:								

		Unit: lux						
Condition		Shutter Speed						
		-	-	-	-	-	-	-
Day mode (Color)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Night mode (B/W)	50 IRE	-	-	-	-	-	-	-
	30 IRE	-	-	-	-	-	-	-
Common Condition:								

Product No. SNC-WR602		As of January 23, 2014						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	1.0	0.50	0.27	0.14	0.067	0.034	-
	30 IRE	0.4	0.2	0.2	0.06	0.03	0.02	-
Night mode (B/W)	50 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
	30 IRE	0.01	0.005	0.003	0.002	0.0007	0.0004	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-WR630		As of January 20, 2015						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.4	0.2	0.2	0.06	0.03	0.02	-
	30 IRE	0.24	0.12	0.064	0.032	0.016	0.0080	-
Night mode (B/W)	50 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
	30 IRE	0.018	0.0090	0.0048	0.0024	0.0012	0.00060	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-WR632C		As of January 20, 2015						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.4	0.2	0.2	0.06	0.03	0.02	-
	30 IRE	0.24	0.12	0.064	0.032	0.016	0.0080	-
Night mode (B/W)	50 IRE	0.03	0.02	0.008	0.004	0.002	0.001	-
	30 IRE	0.018	0.0090	0.0048	0.0024	0.0012	0.00060	-
Common Condition: VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-XM632		As of July 25, 2014						
		Unit: lux						
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Night mode (B/W)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Common Condition: F2.0, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps								

Product No. SNC-XM637				As of July 25, 2014				
				Unit: lux				
Condition		Shutter Speed						
		1/30 sec	1/15 sec	1/8 sec	1/4 sec	1/2 sec	1/1 sec	
Day mode (Color)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Night mode (B/W)	50 IRE	0.30	0.15	0.080	0.040	0.020	0.010	-
	30 IRE	0.18	0.090	0.048	0.024	0.012	0.0060	-
Common Condition:		F2.0, View-DR OFF, VE OFF, AGC ON, 1/30 s, 30 fps						